



SDEC Water Cooled Diesel Generator Set 50kW Three Phase

Our Product Introduction

Basic Information

- Place of Origin: CHINA
- Brand Name: DELLENT
- Certification: CE/ISO9001
- Model Number: DE-SC35~SC76
- Minimum Order Quantity: 1 PC
- Price: bargain face-to-face
- Packaging Details: PLASTIC WRAP OR PLYWOOD CASE
- Delivery Time: 20-30 DAYS
- Payment Terms: L/C, T/T
- Supply Ability: 1 MONTH 600PCS



Product Specification

- Name: Water Cooled Diesel Generator Set
- Engine Brand: SDEC
- Fuel Type: Diesel
- Rated Frequency: 50HZ/60HZ
- Speed: 1500RPM/1800RPM
- Cooling Method: Water-Cooling System
- Warranty: 12 Months/1000 Hours
- Highlight: **SDEC Water Cooled Diesel Generator Set,
Water Cooled Diesel Generator Set 50kW**

for more products please visit us on dellentpower.com

CE SDEC Diesel Generator about 50kW

- 1: The diesel generator should be placed in a well ventilated area to ensure heat dissipation;
- 2: Diesel generators should regularly inspect and replace vulnerable parts such as engine oil and air filter elements to ensure their normal operation;
- 3: When running diesel generators, attention should be paid to the quality and storage method of fuel, to avoid using inferior fuel or improper storage that may cause malfunctions;
- 4: When using diesel generators, appropriate loads should be used according to requirements to avoid overload or underload leading to faults;
- 5: When diesel generators are not used for a long time, regular maintenance and inspection should be carried out to ensure their normal operation;
- 6: Diesel generators should use dry air to avoid malfunctions caused by high humidity;
- 7: Diesel generators should avoid long-term low load operation to avoid affecting the performance of the diesel engine;
- 8: Diesel generators should be avoided in high-altitude areas to avoid affecting the performance of the diesel engine;
- 9: Diesel generators should be avoided from being used in high-temperature environments to avoid affecting the performance of the diesel engine;
- 10: Diesel generators should be avoided in environments with high levels of dust to avoid affecting heat dissipation.

. PRODUCT

50 Hz TECHNICAL DATA										
Specifications 50Hz 400-230V				General specifications						
GENSETS	Prime Power		Standby Power		Engine type	Engine Power kW	Cyl.	Bore mm	Stroke mm	Gov.
	kW	kVA	kW	kVA						
DE-SC35	25	31	28	35	4H4.3-G21	33	4L	105	124	Electric
DE-SC51	37	46	41	51	4H4.3-G22	46	4L	105	124	Electric
DE-SC63	45	56	50	63	4HT4.3-G21	56	4L	105	124	Electric
DE-SC76	55	69	61	76	4HT4.3-G22	68	4L	105	124	Electric
DE-SC94	68	85	75	94	4HT4.3-G23	86	4L	105	124	Electric
DE-SC110	80	100	88	110	4HTAA4.3-G21	105	4L	105	124	Electric
DE-SC124	90	113	99	124	4HTAA4.3-G23	116	4L	105	124	Electric
DE-SC138	100	125	110	138	4HTAA4.3-G22	132	4L	105	124	Electric
DE-SC138	100	125	110	138	4HTAA4.3-G36	140	4L	105	124	ECU
DE-SC151	110	138	121	151	6HTAA6.5-G21	141	6L	105	124	Electric
DE-SC165	120	150	132	165	6HTAA6.5-G22	155	6L	105	124	Electric
DE-SC206	150	188	165	206	6HTAA6.5-G23	185	6L	105	124	Electric
DE-SC220	160	200	176	220	6DTAA8.9-G21	204	6L	114	144	Electric
DE-SC248	180	225	198	248	6DTAA8.9-G24	228	6L	114	144	Electric
DE-SC261	190	238	209	261	6DTAA8.9-G22	242	6L	114	144	Electric
DE-SC275	200	250	220	275	6DTAA8.9-G23	253	6L	114	144	Electric
DE-SC303	220	275	242	303	6ETAA10.4-G21	280	6L	128	144	Electric
DE-SC316	230	288	253	316	6ETAA10.4-G22	294	6L	128	144	Electric
DE-SC385	280	350	308	385	6ETAA11.8-G21	338	6L	128	153	Electric
DE-SC413	320	375	330	413	6ETAA11.8-G31	380	6L	128	153	Electric
DE-SC481	350	438	385	481	6ETAA12.8-G21	420	6L	128	153	Electric
DE-SC481	350	438	385	481	6ETAA12.8-G31	420	6L	128	153	ECU
DE-SC550	400	500	440	550	6KTAA25-G36	506	6L	170	185	ECU
DE-SC633	460	575	506	633	6KTAA25-G35	572	6L	170	185	ECU
DE-SC701	510	638	561	701	6KTAA25-G34	629	6L	170	185	ECU
DE-SC756	550	688	605	756	6KTAA25-G33	684	6L	170	185	ECU
DE-SC853	620	775	682	853	6KTAA25-G32	754	6L	170	185	ECU
DE-SC894	650	813	715	894	6KTAA25-G31	800	6L	170	185	ECU

SDEC OLD

DE-SC69SC	50	63	55	69	SC4H95D2	68	4L	105	124	Electric
DE-SC94SC	68	85	75	94	SC4H115D2	86	4L	105	124	Electric
DE-SC124SC	90	113	99	124	SC4H162D2	116	4L	105	124	Electric
DE-SC138SC	100	125	110	138	SC4H182D2	132	4L	105	124	Electric
DE-SC179SC	130	163	143	179	SC7H222D2	165	6L	114	135	Electric
DE-SC187SC	136	170	150	187	SC7H232D2	170	6L	105	124	Electric
DE-SC206SC	150	188	165	206	SC7H250D2	185	6L	105	124	Electric
DE-SC227SC	165	206	182	227	SC8D282D2	204	6L	114	135	Electric
DE-SC248SC	180	225	198	248	SC9D310D2	228	6L	114	144	Electric
DE-SC275SC	200	250	220	275	SC9D340D2	255	6L	114	144	Electric
DE-SC303SC	220	275	242	303	SC10E380D2	280	6L	128	135	Electric
DE-SC344SC	250	313	275	344	SC12E420D2	308	6L	128	153	Electric
DE-SC375SC	280	350	300	375	SC12E460D2	338	6L	128	153	Electric
DE-SC495SC	360	450	396	495	SC25G610D2	445	12V	135	150	Electric
DE-SC550SC	400	500	440	550	SC25G690D2	505	12V	135	150	Electric
DE-SC619SC	450	563	495	619	SC27G755D2	560	12V	135	155	Electric
DE-SC688SC	500	625	550	688	SC27G830D2	610	12V	135	155	Electric
DE-SC756SC	550	688	605	756	SC27G900D2	662	12V	135	155	Electric

For more models up to DE-SC1375SC, kindly contact our sales.

. Why Choose Us:

Dedicated

We are DEDICATED to meet Customers' need.

Enthusiasm

We respond to our Customers' ENTHUSIASM

Loyalty

We cherish our Customers' LOYALTY

Luxury

We aim to establish our own LUXURY brand

Efficient

We offer our EFFICIENT service

Newest

We adopt NEWEST technologies for products

Trust

We strive for winning the TRUST from Customers

. QUALIFICATION CERTIFICATE:



. FACTORY INTERIOR:



Fuan Dellent Electric & Machinery Co., Ltd.

+8613706938606

jennifer@dellent.com

dellentpower.com

NO.7,JINYE ROADTIEHU INDUSTRIAL AREA CHENGYANG TOWN, FUAN

